

Xerox® VersaLink® B7035 Multifunction Printer



Configuration Report

Custom Paper Type 3	""	Manual Address	Disabled
Custom Paper Type 4	""	DHCPv6	Disabled
Custom Paper Type 5	""	Purpose	Configuration Data
Banner Pages		Auto Configure	
Sensing Separator Page	Disabled	Link-Local Address	"fe80::9e93:4eff:fe9a:34bc"
Print Banner Pages	Off	Auto Stateless Address 1	""
Paper Tray	Tray 1	Auto Stateless Address 2	""
Default Print Paper Size	8.5 x 11"	Auto Stateless Address 3	""
Information Pages Paper Supply	Auto	Auto Stateful Address 1	""
Paper Size Preference	Inch	Automatically Configured Gateway	
Measurement Units	Inches	Address	""
PostScript		IP Address Filtering	Disabled
Sys/Start Job	Enabled	Status	Ready
Error Sheets	Disabled	DNS	
PCL		IPv6 Priority over IPv4 at Domain	
Pitch Size	10.00	Name Resolution	Enabled
Point Size	12.00	Domain Name	""
Font Name	Courier	IPv4	
Lines Per Page	60	DHCP	Disabled
Fax Service		Preferred Server	"10.14.145.5"
Fax Line 1	917732796891	Alternate Server 1	"10.4.145.9"
		Alternate Server 2	""
		Dynamic DNS Registration	Disabled
		IPv6	
		DHCPv6-lite	Enabled
Scan Service		Preferred Server	""
Email		Alternate Server 1	""
Default "From" Address		Alternate Server 2	""
Allow to enter a different address	No	Dynamic DNS Registration	Disabled
Auto Send to Self	Off	Proxy Server (LAN1)	
		Enable Proxy Server	Yes
		Setup	Automatic
		SSL/TLS	
Connectivity		HTTP - SSL/TLS Communication	Disabled
Mobile Workflows		LDAP - SSL/TLS Communication	Disabled
AirPrint	Enabled	Verify Remote Server Certificate	Disabled
Google Cloud Print	Disabled	S/MIME	
Mopria	Enabled	S/MIME Communication	Disabled
USB 3.0		Receive Untrusted Email	Yes
Port Status	Enabled	Message Digest Algorithm	SHA-1
Print From	Enabled	Message Encryption Algorithm	3DES
Scan To	Enabled	Digital Signature - Outgoing Email	Do Not Add
NFC	Enabled	Signing Certificate for Emails	Smart Card Certificate
Ethernet		Certificate Auto Store	Off
Rated Speed	Auto	IPsec	
MAC Address	"9C:93:4E:9A:34:BC"	IPsec Communication	Disabled
TCP/IP		IEEE 802.1X	
IP Mode	Dual Stack	IEEE 802.1X	Disabled
IPv4		Certificate Validation	
Mode	STATIC	Certificate Path Validation	Disabled
IP Address	"10.67.80.239"		
Subnet Mask	"255.255.255.192"		
Gateway Address	"10.67.80.193"		
IP Address Filtering	Disabled		
Status	Ready		
IPv6			